



STATIONARY THRESHER

TECHNICAL SPECIFICATIONS

SYSTEM	STANDARD	OPTION
Power System	Kama Reis 20 Hp Water Cooled Diesel Engine with Starter	1- 15 KW 380 V Electric engine 2-Pto Shaft Tractor Connection (540 rpm)
Fuel Tank	40 lt.	-
Threshing Width	500 mm	800 mm
Vari-Drive RPM Range	300 rpm-2200 rpm Adjustable by variator.	-
Upper Sifter Area	0.60 m ²	-
Lower Sifter Area	0.50 m ²	-
Lower Sifter Dimensions	5x10 mm - 8x16 mm - 10x20 mm	2x4 mm - 15x30 mm (Custom manufacture as
Number of Concave Bars	7	-
Concave Wire Width	6 mm	10 mm - 14 mm
Concave Winding Angle	117°	-
Concave Wire Diameter	3 mm	-
Threshing Area	0.15 m ²	-
Vari-Drive Diameter	300 mm	-
Number of Vari-Drive Bars	6	-
Packaging System	Manual Bagging	Pneumatic Bagging
Cleaning Fan	500 - 1500 rpm (Mechanical Variator	-

DIMENSIONS

	STANDARD
Weight	600 kg
Width	1450 mm
Length	2700 mm
Height	1950 mm
Tire Sizes	145 / 70 R12
Shipping	By Towing Hook, Max. speed 20 km/h, OPT: 80 km/h